

FAST AND EASY FEATHER-TOUCH DISASSEMBLY

GO-GO[®] ULTRA X

The Go-Go[®] Ultra X is loaded with design features like one-hand feather-touch disassembly and a convenient drop-in battery box that makes transport and travel worry free. The Go-Go Ultra X delivers these features and more, along with the performance you expect from the first name in travel mobility, making it the ultimate travel scooter value.

GO-GO ELITE TRAVELLER[®] PLUS

The Go-Go Elite Traveller[®] Plus was designed to bring travel scooters to a greater range of people than ever before. An increase in length and width, and a weight capacity of 147 kg (325 lbs.) combine with a wraparound easy-drive tiller to allow both the larger individual and those with limited dexterity to experience the benefits of a travel-specific mobility product for the first time. Featuring seat post suspension for a smoother ride and one-hand feather-touch disassembly make the Go-Go Elite Traveller Plus the easiest travel scooter to take along anywhere.



Go-Go[®] Ultra X
4-wheel



Go-Go[®] Ultra X
3-wheel



Go-Go[®] Elite Traveller Plus
4-wheel

Go-Go® Ultra X	3-wheel	4-wheel	Go-Go Elite Traveller® Plus 4-wheel
Weight capacity:	118 kg (260 lbs.)	118 kg (260 lbs.)	147 kg (325 lbs.)
Maximum speed ² :	Up to 6 km/h (4 mph)	Up to 6 km/h (4 mph)	Up to 6 km/h (4 mph)
Ground clearance ¹ :	3.5 cm (1.375")	3.5 cm (1.375")	7.62 cm (3") at midframe
Turning radius ¹ :	82.5 cm (32.5")	112 cm (44.125")	116 cm (45.75")
Overall length ¹ :	94 cm (37")	101 cm (39.75")	101 cm (39.75")
Overall width ¹ :	49.5 cm (19.5")	49.5 cm (19.5")	54 cm (21.125")
Tyres:			
Front:	5 cm x 20 cm (2" x 8") solid	5 cm x 18 cm (2" x 7") solid	5 cm x 20 cm (2" x 8") solid
Rear:	6.35 cm x 20 cm (2.5" x 8") solid	6.35 cm x 20 cm (2.5" x 8") solid	8 cm x 23 cm (3" x 9") solid
Anti-tips:	Rear	Rear	Rear
Transport weight:			
Total weight w/o battery pack:	34 kg (75 lbs.)	35.5 kg (78.5 lbs.)	39.5 kg (87 lbs.)
Heaviest piece when disassembled:	13 kg (28 lbs.) (front section)	15 kg (33.5 lbs.) (front section)	16 kg (35 lbs.) (front section)
Drive system:	24-volt DC motor, sealed mini-transaxle		
Dual braking system:	Electronic, regenerative, and electromechanical		
Standard seating:	Foldable, compact, vinyl-covered molded plastic		
Battery charger:	Off-board, 2-amp		
Per-charge range ² :	Up to 12.87 km (8 miles) ⁵		Up to 23 km (14 miles)
Battery requirements:	Two 12-volt, deep cycle (standard)		
	Size: Go-Go Ultra X: 2 x 12 AH ⁴ Go-Go Elite Traveller Plus: 2 x 18 AH ⁴ (standard)		
	Weight ³ : Go-Go Ultra X: 12 AH: 9 kg (20 lbs.) battery pack Go-Go Elite Traveller Plus: 18 AH: 13 kg (29 lbs.) battery pack		

Go-Go Ultra X Standard Colour:



Red

Go-Go Elite Traveller Plus Standard Colours:



Red



Blue

2 sets of exciting colours
with every scooter!

- Features** (of all)
- Feather-touch disassembly permits simple frame separation with only one hand
 - Pride's exclusive black, non-scuffing tyres
 - Auto-connecting front to rear cable
 - Front frame-mounted seat post offers maximum stability
 - All-new frame design easily disassembles into 5 super lightweight pieces for convenient transport and storage
 - Modular design for easy serviceability
 - Convenient off-board dual voltage charger can charge battery pack on-board or off-board
 - Front tiller-mounted basket

Features (Go-Go ET Plus only)

- Seat post suspension
- Easy-drive tiller with wraparound handles
- 23 cm (9") rear wheels
- 147 kg (325 lbs.) weight capacity
- Includes 2 sets of easily changeable coloured panels - Red & Blue
- Microprocessor-based controller offers optimal power management and added safety features
- Removable footboard basket for additional storage

FEATHER-TOUCH DISASSEMBLY



¹ Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.

² Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

³ Battery weight may vary based on manufacturer.

⁴ AGM or gel-cell type required.

⁵ This range was obtained with the 4-wheel model.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.